

EXPERIENCE THE
ALLIANCE
DIFFERENCE



Alliance
emerald
ENERGY-SAVING



R32 Inverter Midwall Split Air conditioner

- Heating and Cooling
- Flash Cooling – Cool function Boost Function
- LED temperature display
- Self-Diagnosis
- Refrigerant Leakage Detection
- Low noise operation
- Wi-fi compatible
- Pipe-kit included



Alliance Emerald R32 Inverter



Alliance
emerald
ENERGY-SAVING

The Emerald midwall split is an attractive unit in any space. With high cooling and heating capacities, as well as an EER of 3 and COP of 3.2, this midwall split is suitable for climate control of large indoor areas. A low indoor noise level of 28.5 dB(A) (on low setting) ensures exceptional quietness of operation. As with all Alliance models, the Comfee range is backed by branches nationwide.



Indoor			FOUSI09-R32	FOUSI12-R32	FOUSI18-R32	FOUSI24-R32	
Power supply		V-Ph-Hz	220_230V_1Ph,FREQUENCY_50HZ	220_240V_1Ph,FREQUENCY_50HZ	220V_1Ph,FREQUENCY_50HZ	220V_1Ph,FREQUENCY_50HZ	
Cooling (Standard conditions)	Capacity	W	2600	3500	5300	7000	
	Input	W	824	1144	1627	2220	
	Current	A	3.58	5.03	7.48	9.65	
	EER	W/W	3.2/A	3.1/B	3.2/A	3.2/A	
Heating (Standard conditions)	Capacity	W	2600	3600	5300	7000	
	Input	W	775	1015	1550	1901	
	Current	A	3.44	4.5	7.1	8	
	COP	W/W	3.4	3.61	3.4	3.70	
Rated Power Input		W	2200	2070	2950	2850	
Rated Current		A	10.5	9.2	13.5	13.5	
Starting current		A	/	0	0	0	
Compressor	Capacity	W	2300 ±3%	2035/3255	4385	4730	
	Input	W	605 ±3%	325/826	1140	1250	
	Rated current(RLA)	A	4.20 ±3%	2.40/5.65	7.50	8.10	
Indoor fan motor	Input	W	43	/	71	77	
	Capacitor	uF	1.5	1.5	1.5	3	
	Speed(Hi/Mi/Lo)	r/min	1150/890/760	1150/940/735	1200/980/650	1200/1040/880	
Indoor coil	a.Number of rows		2	2	2	2	
	b.Tube pitch(a)x row pitch(b)	mm	21x13.37	21x13.37	21x13.37	21x13.37	
	c.Fin spacing	mm	1.2/1.3	1.2/1.3	1.2	1.3	
	d.Fin type (code)		Hydrophilic aluminium	Hydrophilic aluminium	Hydrophilic aluminium	Hydrophilic aluminium	
	e.Tube outside dia.and type	mm	Ø7,innergroove tube	Ø7,innergroove tube	Ø7,Inner groove tube	Ø7,Inner groove tube	
	f.Coil length x height x width	mm	525x84x13.37+525x105x26.74+525x105x26.74	525x84x13.37+525x105x26.74+525x105x26.74	750x210x26.74+750x126x26.74	820x210x26.74+820x126x26.74	
	g.Number of circuits		2	2	4	4	
Indoor air flow (Hi/Mi/Lo)		m3/h	534/397/332	520/440/400	760/580/490	1150/940/850	
Indoor noise level (Hi/Mi/Lo)		dB(A)	40.0/34/32	38.5/34.5/23.5	44.5/38/34.5	49.5/44/36.5	
Indoor unit	Dimension(W*D*H)	mm	729x200x292	729x200x292	971x228x321	1082x234x337	
	Packing (W*D*H)	mm	790x270x375	790x270x375	1045x305x405	1155x415x315	
	Net/Gross weight	kg	8.2/10.5	8.1/10.3	11.7/15	14.1/17.8	
Outdoor			FOUSI09X-R32	FOUSI12X-R32	FOUSI18X-R32	FOUSI24X-R32	
Outdoor fan motor		Speed	r/min	810/700	800/700/600	850/550	900/700/550
Outdoor coil	a.Number of rows		1	1	2	2	
	b.Tube pitch(a)x row pitch(b)	mm	21x22	21x13.37	21x13.37	21x22	
	c.Fin spacing	mm	1.3	1.4	1.4	1.3	
	d.Fin type (code)		Unhydrophilic aluminium	Hydrophilic aluminium	Hydrophilic aluminium	Hydrophilic aluminium	
	e.Tube outside dia.and type	mm	Ø7,Inner groove tube	Ø7,Inner groove tube	Ø7,Inner groove tube	Ø7,Inner groove tube	
	f.Coil length x height x width	mm	600x420x22	750x462x13.37	755*504*13.37+735*504*13.37	860*504*44	
	g.Number of circuits		2	2	4	6	
Outdoor air flow		m³/h	1300	1800	2100	2500	
Outdoor noise level		dB(A)	52.5	56	57	57.5	
Outdoor unit	Dimension(W*D*H)	mm	668x252x469	720x270x495	765x303x555	805x330x554	
	Packing (W*D*H)	mm	765x270x525	835x300x540	887x337x610	915x370x615	
	Net/Gross weight	kg	18.5/19.9	21.4/23.2	27.5/29.9	33/35.6	
Refrigerant type		kg	R32/0.47	R32/0.58	R32/1.02	R32/1.25	
Design pressure		MPa	4.2/1.5	4.3/1.7	4.3/1.7	4.3/1.7	
Refrigerant piping	Liquid side/ Gas side	mm(inch)	6.35mm(1/4in)/9.52mm(3/8in)	6.35mm(1/4in)/9.52mm(3/8in)	6.35mm(1/4in)/12.7mm(1/2in)	9.52mm(3/8in)/15.9mm(5/8in)	
	Max. refrigerant pipe length	m	25	25	30	30	
	Max. difference in level	m	10	10	20	20	
Connection wiring			1.5x4//	1.5x4//	1.5x4//	1.5x4//	
Plug type			1.5x3/VDE plug	1.5x3/VDE plug	1.5x3/Argentinian 3 Pins Plug	//no-plug	
Thermostat type			(Remote Control)	(Remote Control)	(Remote Control)	(Remote Control)	
Operation temperature (According to remote control setting)			C°	17-30	17-30	17-30 17-30	
Room temperature	Indoor(cooling/ heating)	C°	16-32/0-30	16-32/0-30	16-32/0-30	16-32/0-30	
	Outdoor(cooling/heating)	C°	0-50/-15-24	-15-50/-15-24	0-50/-15-24	0-50/-15-24	
Application area (Cooling Standard)		m²	12-18	16-23	24-35	29-43	

Alliance reserves the right to discontinue or change specifications at any time without notice and without incurring obligation. E&OE.